

HIGH CURRENT POWER INDUCTOR

大电流功率模压电感

■ XAL5020

Features

- Compact size using flat wire, and SMD type.
扁平线小尺寸封装，贴片类型
- Low radiation noise by magnetically shielded construction
闭合磁路封装，低辐射
- High current, Low resistance.
大电流，低电阻
- Operating temperature : -40°C ~ +125°C.
工作温度：-40°C ~ +125°C



Applications

- high efficiency DC/DC converters. 高效 DC/DC 转换器
- Single and polyphase buck converters. 单相、多相降压转换器
- Filter for audio applications. 音频滤波应用
- Optimized for high current boost applications. 大电流升压应用优化


Electrical characteristics

Part number 料号	Inductance 电感量 μH (± 20%)	DC resistance 直流电阻 mΩ max		Temperature rise current 温升电流 A.		DC saturation current 直流饱和电流 A max. $\Delta L \leq 30\%$
		Typ	max	$\Delta T \leq 20^\circ\text{C}$	$\Delta T \leq 40^\circ\text{C}$	
XAL5020-161	0.16	4.11	5.00	13.9	18.8	24.2
XAL5020-331	0.31	6.40	7.68	10.9	14.4	17.1
XAL5020-561	0.56	8.30	9.54	9.9	13.9	14.1
XAL5020-801	0.80	10.3	11.8	9.4	13.0	12.0
XAL5020-122	1.2	17.8	20.5	6.8	9.4	9.5

Remark

- Inductance is measured with a LCR meter 4284A or equivalent.
Test frequency at 100kHz
- DC resistance is measured with 16502 Milliohm Meter , or equivalent.
Reference ambient temperature 25°C

Recommended Land Pattern (mm)



Dimensions

